



Specifications	<b>Gross Capacity</b>	210 L (7.42 Cu.Ft)
	<b>Net Capacity</b>	198 L (6.99 Cu.Ft)
	<b>Gross Weight</b>	68 kg (149.9 lbs)
	<b>Net Weight</b>	65 kg (143.3 lbs)
	<b>Adjustable Shelf</b>	Wire, 2 Pieces
	<b>Shelf Dimension (WxD)</b>	453x612 mm (17.8"x24.1" inch)
	<b>Interior Dimension (WxDxH)</b>	465x680x840 mm (18.3"x26.8"x33.1" inch)
	<b>Exterior Dimension (WxDxH)</b>	585x790x990 mm (23"x31.1"x39" inch)
	<b>Packing Dimension (WxDxH)</b>	625x830x1070 mm (24.6"x32.7"x42.1" inch)
	<b>Loading (20GP / 40GP / 40HQ)</b>	50 / 104 / 104 Pieces
Systems	<b>Certificates</b>	CE / CB / RoHS
	<b>Cooling System</b>	Dynamic Cooling
	<b>Inside Temperature</b>	≤ -18 °C (≤ -0.4 °F)
	<b>Temperature Control</b>	Digital
	<b>Climate Class</b>	N
	<b>Voltage / Frequency</b>	220~240V/50Hz
	<b>Input Power</b>	W
	<b>Rated Current</b>	A
	<b>Refrigerant</b>	R290
	<b>Energy Consumption</b>	KW.h/24h
	<b>Compressor</b>	Cubigel
	<b>Compressor Power (W / HP)</b>	W
	<b>Evaporator</b>	Fin-blade Type
Components	<b>Evaporator Fan</b>	2 Pieces
	<b>Condenser</b>	Wire Type
	<b>Condenser Fan</b>	1 Piece
	<b>Foaming Agent</b>	Cyclopentane (C5H10)
	<b>Body Color</b>	Black or White
	<b>Interior Finishing</b>	Painted Galvanized Steel
	<b>Exterior Finishing</b>	Painted Steel
	<b>Canopy LED Light</b>	No
	<b>Interior LED Light</b>	1 Piece, Max 3W
	<b>Glass Door</b>	3 Layers Hollow Tempered Heating Glass
	<b>Door Material</b>	PVC
<b>Self-closing Door</b>	Optional	
<b>Handle</b>	Recessed	
<b>Lock &amp; Key</b>	Optional	
<b>Water Tray</b>	Self-evaporation	
<b>Caster</b>	4 Adjustable Legs	

• Due to the technology update, we reserve the right to change the parameters prior to notice.



<b>Specifications</b>	<b>Gross Capacity</b>	80 L (2.8 Cu.Ft)
	<b>Net Capacity</b>	80 L (2.8 Cu.Ft)
	<b>Gross Weight</b>	50 kg (110 lbs)
	<b>Net Weight</b>	48 kg (105.6 lbs)
	<b>Adjustable Shelf</b>	Wire, 2 Pieces
	<b>Shelf Dimension (WxD)</b>	354x303 mm (13.9"x11.9" inch)
	<b>Interior Dimension (WxDxH)</b>	373×345.5×653 mm (14.7"×13.6"×25.7" inch)
	<b>Exterior Dimension (WxDxH)</b>	490×480×1030 mm (19.3"×18.9"×40.6" inch)
	<b>Packing Dimension (WxDxH)</b>	540×530×1110 mm (21.3"×20.9"×43.7" inch)
	<b>Loading (20GP / 40GP / 40HQ)</b>	88 / 176 / 176 Pieces
<b>Systems</b>	<b>Certificates</b>	CE / CB / RoHS
	<b>Cooling System</b>	Static Cooling
	<b>Inside Temperature</b>	≤ -18 °C (≤ 0.4 °F)
	<b>Temperature Control</b>	Manual
	<b>Climate Class</b>	N
	<b>Voltage / Frequency</b>	220~240V/50Hz
	<b>Input Power</b>	210 W
	<b>Rated Current</b>	1.5 A
	<b>Refrigerant</b>	R290 (27g)
	<b>Energy Consumption</b>	1.0 KW.h/24h
	<b>Compressor</b>	WANBAO FTA55L
	<b>Compressor Power (W / HP)</b>	735 W
	<b>Evaporator</b>	Skin Type
	<b>Evaporator Fan</b>	Optional
<b>Components</b>	<b>Condenser</b>	Wire Type
	<b>Condenser Fan</b>	Square Fan, 1 Piece
	<b>Foaming Agent</b>	Cyclopentane (C5H10)
	<b>Body Color</b>	Black or White
	<b>Interior Finishing</b>	Painted Aluminum Steel
	<b>Exterior Finishing</b>	Painted Steel
	<b>Canopy LED Light</b>	2835, Max 3W
	<b>Interior LED Light</b>	2835, Max 3W
	<b>Glass Door</b>	3 Layers Hollow Tempered Heating Glass
	<b>Door Material</b>	PVC
	<b>Self-closing Door</b>	Optional
	<b>Handle</b>	Extruded
<b>Lock &amp; Key</b>	Optional	
<b>Water Tray</b>	Self-evaporation	
<b>Caster</b>	4 Adjustable Legs	

• Due to the technology update, we reserve the right to change the parameters prior to notice.