



Specifications	Gross Capacity	160 L (5.7 Cu.Ft)
	Net Capacity	154 L (5.5 Cu.Ft)
	Gross Weight	78 kg (172 lbs)
	Net Weight	75 kg (165.3 lbs)
	Adjustable Shelf	Wire, 5 Pieces
	Shelf Dimension (WxD)	295x327 mm (11.6"x12.9" inch)
	Interior Dimension (WxDxH)	300x315x1450 mm (11.8"x12.4"x57.1" inch)
	Exterior Dimension (WxDxH)	440x510x1880 mm (17.3"x20.1"x74" inch)
	Packing Dimension (WxDxH)	490x560x1940 mm (19.3"x22"x76.4" inch)
	Loading (20GP / 40GP / 40HQ)	44 / 96 / 120 Pieces
	Certificates	CE / CB / RoHS
Systems	Cooling System	Dynamic Cooling
	Inside Temperature	≤ -18 °C (≤ 0.4 °F)
	Temperature Control	Digital
	Climate Class	N
	Voltage / Frequency	220~240V/50Hz
	Input Power	405 W
	Rated Current	2.7 A
	Refrigerant	R290 (86 g)
	Defrost Power	270 W
	Compressor	WANBAO FNA100
	Evaporator	Fin-blade Type
	Evaporator Fan	Axial Flow Fan, 1 Piece
	Condenser	Skin+Wire Type
Condenser Fan	Square Fan, 1 Piece	
Components	Foaming Agent	Cyclopentane (C5H10)
	Body Color	Black or White
	Interior Finishing	Painted Galvanized Steel
	Exterior Finishing	Painted Steel
	Canopy LED Light	2835, Max 3W
	Door LED Light	2835, Max 9W, Vertical
	Glass Door	3 Layers Hollow Tempered Heating Glass
	Door Material	PVC
	Self-closing Door	Yes
	Handle	Extruded
	Lock & Key	Yes
Water Tray	Self-evaporation	
Caster	4 Adjustable Legs	

• Due to the technology update, we reserve the right to change the parameters prior to notice.